



► Features



Whole Aluminum alloy body

Both the base and the outer box are made of durable aluminum alloy materials



Innovative design

- ① All cables are Hidden
- ② Back Cover adopts magnet link, no screws



Modular MSR

Adopts USB connector
Easy to disassemble and install



Rich interfaces

Meet multiple needs (Intel Celeron J3455)



► Options



Modular design



Modular design
VFD 2x20



Modular design
12inch 4:3

► Package

Packing box save more than 30% shipping cost



Bottom plate is disassembled
in packing box



► Product show



N9		Specification		
Main Board	Processor	Intel Celeron J3455	Intel Celeron J4125	Intel Core 5th gene. i5
	Chipset	SOC		
	Memory	Onboard LPDDR4 4G	1 x DDR4 SO-DIMM 4G (Max. 8GB)	1 x DDR3L SO-DIMM 4G (Max. 8GB)
	Storage	1 x M.2 SATA SSD 64G/128G		1 x M.SATA SSD 64G/128G
	OS Support	win7 win8 win10		
	Default OS	Windows 10 IoT Enterprise LT5B (trial version)		
	LCD Size	15" TFT LCD (LED backlight) 4:3		
Display & Touch	Resolution	1024(RGB) x 768		
	Brightness	350cd/m²		
	Contrast ratio	700:1(Typ.)(transmission)		
	Touch screen	Pure flat surface capacitance 10 point multi-touch		
	Display area	304.1 x 228.1mm		
I/O & Expansion	CPU model	Interl Celeron J3455	Intel Celeron J4125 Intel Core 5th gene. i5	
	Standard USB	6xUSB 2.0 (2 in Shell)		6xUSB 2.0 (2 in Shell)
	HDMI	1		/
	COM	1		1
	1x12V DCOut	1		1
	VGA	1		1
	LAN	1 x LAN RTL 8111H (Support 100/1000Mbps) by RJ-45		
	PS/2	1		1
	VFD2x20 Display Port	1		1
Power	External power adapter, 60W/12V (Lock type)			
Certificates	CE, Rohs, FCC			
Wall Mount	VESA 75 x 75mm			
Peripheral	MSR	LIF-MSR006ISO7811		
	RFID	LIF-RD01 supports mifare one S50,S70 and its compatible TYPE A and B cards		
	IC	LIF-PC/SC supports standard HID protocol and PC/SC protocol		
	IBUTTON-A	comply with the 1-wire protocol		
	Customer dispaly	12.1 inch 4:3(800x600)		15 inch 4:3(1024x768)
	VFD	2x20 LED		
	WIFI	11N wireless 300Mbps		
	4G	Optional		
	Speaker	Optional		
Package size		430x290x430mm		
Gross Weight		8KG (Single Display)		
		8.3KG (with VFD2*20)		
		9.7KG (with 12.1" customer display)		
		10.7KG (with 15" customer display)		
Certification		CE,FCC,ROHS		

● Client Cases

