



Direct thermal Printer


PP58

- Headlamp key design
- Support QR code printing
- Support IAP online upgrade
- Support print density adjustment



PP58

Direct thermal Printer



Model PP58	
Printing method	Direct thermal
Paper width	57.5±0.5mm
Print width	48 mm
Column capacity	384 dots/line
Printing speed	90 mm/s
Interface	USB / USB+Bluetooth
Line spacing	3.75mm (Adjustable by commands)
Fonts Symbology	
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24
Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 / QR code
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
Input buffer	128 Kbytes
NV Flash	1M bytes
Power	
Power adaptor	AC 100V/240V, 50 ~ 60Hz
Power source	DC 9V / 2A
Cash drawer	DC 12V / 1A
Physical characteristics	
Weight	0.45kg
Dimensions	138.77 * 122 * 93.3mm
Environmental Requirements	
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)
Reliability	
Printer head life	50Km
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/Android/Mac
SDK	iOS, Android, Windows

